

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



(19)

(11) Publication number:

**61159217 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **59280050**(51) Intl. Cl.: **B21C 3/08 B21C 1/12**(22) Application date: **29.12.84**

(30) Priority:

(43) Date of application  
publication: **18.07.86**(84) Designated contracting  
states:(71) Applicant: **ASAHI CHEM IND CO LTD**(72) Inventor: **TANAKA MASAO  
SAITO AKIRA**


(74) Representative:

**(54) HIGH SPEED WIRE  
DRAWING EQUIPMENT  
OF WIRE ROD**

(57) Abstract:

**PURPOSE:** To keep always the wire drawing diameter constant at the high speed wire drawing time by transmitting the output of a wire diameter detecting mechanism to a rolling reduction control mechanism and by correcting automatically the rolling reduction mechanism of a roller die accordingly.

**CONSTITUTION:** A wire rod 1 is drawn in two steps by an oval groove roller dies 3a, 3b and round grooved roller dies 4a, 4b. A wire drawing material 1' is directed for a cutter with being straightened by a straight liner but the wire diameter of the wire drawing material 1' is detected by a wire diameter detector 2 before that and the detection signal is transmitted to two axes controllers 9, 10. The controllers 9, 10 output to pulse motors 7a, 8a, 7b, 8b as a correction signal the pulse in the frequencies operated so as to enter within the allowable range the deviation between the measured value and set value of the inputted wire diameter with their comparison. The motors 7a, 8a, 7b, 8b are driven according to the input signal and the rolling reduction of the dies 3a, 4a and dies 3b, 4b are corrected.



COPYRIGHT: (C)1986,JPO&amp;Japio